



## Standards



TYPE 5  
13982-1



TYPE 6  
13034



EN  
1073-2



EN  
1149-5

## Technical specifications



Self-adhesive zip flap for increased protection



Breathable back panel to help reduce the risk of heat stress



Hood 3 pans allows much greater freedom of movement



Jersey wrist




Triangle of comfort

- Bound seams seal to liquid projections and very tiny dust
- Triangle of comfort at the crotch for a better resistance
- Two-way closing zipper
- Waist elasticated for a better fit
- Strong mechanical resistance during intense work
- Antistatic material treated on both sides to facilitate the dissipation of electrostatic charges

# Material and seams

## SMS AND MICROPOROUS FILM MATERIAL

Provide high breathability and optimum comfort




Breathing fabric's offering a waterproofness to the liquid projections



## BOUND SEAM

Overlay SMS or microporous film fabrics offer a very strong seam. It provides superior strength, a barrier against spray and particule dry



## Applications

- Industrial and automotive painting
- Composite industries
- Handling of glues and solvents
- Agro-food chemical industries
- Insulation works
- Chemical industries

## Technical Data

Resistance to liquids penetration

Chemical properties of the fabric	Test method	Penetration	Repulsion
H <sub>2</sub> SO <sub>4</sub> - Sulphuric acid 30%	EN 368	Class 3	Class 3
NaOH - Sodium Hydroxyde 10%	EN 368	Class 3	Class 3
O Xylene	EN 368	Ø	Ø
Butan-1-ol	EN 368	Ø	Ø

## Tests Results EN 13935-2

Seams strength

Test method	Results	Class
Seams strength – ISO 13935-2	120N	3/6

## Reference

S	M	L	XL	XXL	XXXL
WL-B-01	WL-B-02	WL-B-03	WL-B-04	WL-B-05	WL-B-06

WL-B-0X



X50

