



Standards



Technical Specifications



- Breathable material for a better comfort
- Two-sided antistatic treatment to allow easy dissipation of electrostatic charges
- Raglan sleeve for much greater freedom of movement
- Elasticated ankles and waist for a better fit
- Standardized against radioactive particles
- Standardized against biological risks

Material and Seam


MICROPOROUS FILM MATERIAL

Breathable material impermeable against liquid splashes



STITCHED SEAM

For a high mechanical resistance. Appropriate for light liquid splashes and dry particles



4 THREADS

Applications

- Industrial and automotive painting
- Composite and chemical industries
- Agri-food industries
- Pharmaceutical industries
- Handling of adhesives and solvents
- Industrial cleaning and maintenance

Technical Data

Resistance to liquid penetration

Chemical properties of the material EN ISO 6530

H₂SO₄ - Sulphuric acid 30%
 NaOH - Sodium Hydroxide 10%
 O Xylene
 Butan-1-ol

Penetration

Class 3
 Class 3
 Class 2
 Class 2

Repulsion

Class 3
 Class 3
 Class 3
 Class 3

Seam strength

Test Method EN ISO 13935-2

Results

120 N

Class

3/6

Reference

M	L	XL	XXL	XXXL
WL-P-02	WL-P-03	WL-P-04	WL-P-05	WL-P-06

WL-P-OX



X50

